

DSTNY firewall settings

Notes to observe:

- Make sure that SIP-Inspection / SIP-ALG / SIP-Helper is disabled in the local firewall.
- If services aren't working as expected, please allow the rules from the inside of the local firewall as well.
- Media/Speech is negotiated dynamically in the SDP for every call. Therefore it is necessary to allow the whole port span.

Dstny base functionality:

To	Destination port	Protocol	Transport
Dstny telephony system			
185.39.124.0/22	443	HTTP(S)	TCP
185.39.124.0/22	5060/5061	SIP	TCP/UDP
185.39.124.0/22	10000-65534	RTP/SRTP	UDP

For you with desk phones:

Below displays optional firewall settings if you are using desk phones from Mitel or Snom.

To	Destination port	Protocol	Transport	Rule	Comment
Fixed phones					
1.aastra.pool.ntp.org	123	NTP	UDP	Allow	Used for date/time in fixed phones
2.aastra.pool.ntp.org	123	NTP	UDP	Allow	Used for date/time in fixed phones
3.aastra.pool.ntp.org	123	NTP	UDP	Allow	Used for date/time in fixed phones
0.se.pool.ntp.org	123	NTP	UDP	Allow	Used for date/time in fixed phones
Snom phone provisioning					
185.39.124.0/22	9443	HTTPS	TCP	Allow	Used for provisioning of Snom phones
Snom SRAPS					
52.28.89.237	443	HTTP(S)	TCP	Allow	Snom phone settings distribution
Mitel Phone RCS					
rcs.aastra.com	80 / 443	HTTP(S)	TCP	Allow	Snom phone settings distribution